



Temporary fire doors



Tempus TEMPORARY FIRE DOORS

NEXT GENERATION FIRE PROTECTION



Constructed from heavy-duty steel with a mineral wool core, Tempus is designed to withstand the rigours of a construction site whilst maintaining fire compliance throughout.

Available in two sizes; 1000mm(w) x 2100mm(h) and 1000mm(w) x 2300mm(h).



STANDARD DETAILS

1 60 MINUTE FIRE RATING

> Tested to BS EN1634-1 for resistance to fire

2 FIXING HOLES (FACE-FITTED)

- > Easy access and quick to install
- > Provided with slots to enable the door to be lifted if required without removing all the fixings

3 TRAVEL-BOLT SYSTEM

- > Keeps door closed for easy transportation
- > Holds the exact door gap when installing

4 PULL-HANDLE

No latch required allowing simple and efficient usage by site operatives

5 ADJUSTABLE DOOR CLOSER

- > Ensures the door is always closed after use
- Back check provided to prevent damage to the doorset and the surrounding area when it is opened too fast

6 VISION PANEL

> Provides visibility of anyone coming the other side avoiding any accidents or collisions

7 DURABLE HINGES

> With self lubricating sintered bronze bearings

8 PUSH/KICK PLATE

> Providing additional door protection from the wear-and-tear of daily use

OPTIONAL EXTRAS

DROP-DOWN THRESHOLD SEAL

 Automatic drop-down threshold to provide a complete seal underneath the door.



DEAD LOCK

 Providing additional door security by allowing areas within the building to be closed off.



SPECIAL FEATURE

Sera™

Fire-activated Lock

In the event of a fire the door locks to stop the spread of fire

The unique inert locking system automatically activates when in direct contact with fire, typically between 100-200°C.

Once activated, forced entry is possible for Fire Brigade.



SUSTAINABILITY

As one door closes, another opens!

Tempus is a self-contained, pre-hung unit meaning the doorset can be reused time and time again on multiple projects. By reusing the doorset we can significantly reduce the waste associated with traditional temporary doors.







INSTALLATION

The pre-hung unit makes installation quick and simple. The doorset is face-fitted to the wall, this ensures the doorset can accommodate varying opening sizes. If required, our technical team can assist with any installation queries on-site.





Scan to download installation guide

SUPPORT

No one cares like Selo does about the success of every project, that's why we're the only doorset manufacturer to offer Halo Assist™ providing you with dedicated project support assisting you from initial concept and specification, through to the final execution.





Contact us for support

Our mission is to simplify bespoke and complex building methods

Contact our experienced project consultants: call 020 3880 0339 email sales@selo-uk.com









SEL-MRK-00003

Rev 2.2 - April 2023