


FIRE RATING	FD120
FIRE STOPPING	INTUMESCENT ARCRYLIC SEALANT QUENCH FIRE-STOPPING
ACOUSTIC RATING	N/A 30dB
Results declared reflect the optimum achievable within the limitations of the test standard and sites specific average results may vary where building elements of different materials interface altering natural acoustic deflection.	

Drawing For Information Only  
NOT FOR CONSTRUCTION


ABOVE TO BE SPECIFIED AS REQUIRED

Please note:  
Wall build up to be certified by others.



STRUCTURAL OPENING

EXTERNAL FRAME SIZE



DOOR HEIGHT


LOCK HEIGHT  
FROM BOTTOM  
OF DOOR

FFL

PLEASE NOTE THAT THE PLASTER FINISH HAS NOT BEEN SHOWN FOR SAKE OF CLARITY .

Selo are not the designers responsible for any wall detail if shown, you should know that we are not aware of any fire test evidence for wall constructions which are not, standard as defined in EN1363-1:2020, nor is it our responsibility to establish if such evidence exists. Tested detail in accordance with EN1634-1, requires standard supporting wall constructions with a minimum of 200mm either side and above door frame. Flexible wall construction requirement is a minimum of 300mm between apertures. Minimum upstand in flexible standard wall construction 100mm. Outside of these minimum dimensions specific fire test evidence should be sought. All requirements of the Fire resistance field of application report from Warringtonfire, for the Selo product/s included in this drawing must be ensured, or an alternative fire assessment for any deviation including non-standard wall details must be sought from a competent and designated body for producing fire resistance assessments.

FOR FURTHER TECHNICAL DETAIL AND INFORMATION PLEASE  
CONTACT THE SALES TEAM AT [sales@selo-uk.com](mailto:sales@selo-uk.com)

				Remove all burrs and sharp edges.				FINISH:	N/A		COLOUR:	N/A	
				Please report errors and omissions			PROJECT:	LIGNA - PLASTERED		TOLERANCES IN mm UNLESS OTHERWISE NOTED  X ± 1 X.X ±0.5 ANGULAR ±0.5 DEG			
				MATERIAL:	N/A		INT DWG NO:	SEL-DRW-PRD-LIGN-0002					
					NAME	DATE	EXT DWG NO:						
B	Wall build-up note added.	CK	29/7/22	DRAWN:	GT	10/8/21	DESCRIPTION:	SINGLE RH DOOR - PLASTERED		DO NOT SCALE PRINT			
A	Initial issue		GT	10/8/21	CHECKED:			selo	FINISH		MILLIMETERS	REV.	
REV:	COMMENT:	REVISED BY:	DATE:	APPROVED:			SCALE:		NTS	SHEET:	1 OF 2		B


FIRE RATING	FD120
FIRE STOPPING	INTUMESCENT ARCRYLIC SEALANT QUENCH FIRE-STOPPING
ACOUSTIC RATING	N/A 30dB
Results declared reflect the optimum achievable within the limitations of the test standard and sites specific average results may vary where building elements of different materials interface altering natural acoustic deflection.	

ABOVE TO BE SPECIFIED AS REQUIRED

Please note:  
Wall build up to be certified by others.


Drawing For Information Only  
NOT FOR CONSTRUCTION

PLEASE NOTE THAT THE PLASTER FINISH HAS NOT BEEN SHOWN FOR SAKE OF CLARITY .




Detail A


FIRE STOPPING  
TO BE SPECIFIED.  
TO BE ADDED TO  
ALL 4 SIDES WHERE  
THE LIGNA RISER  
MEETS THE WALL



Detail B




Detail C



Detail D

Selo are not the designers responsible for any wall detail if shown, you should know that we are not aware of any fire test evidence for wall constructions which are not, standard as defined in EN1363-1:2020, nor is it our responsibility to establish if such evidence exists.  
Tested detail in accordance with EN1634-1, requires standard supporting wall constructions with a minimum of 200mm either side and above door frame. Flexible wall construction requirement is a minimum of 300mm between apertures. Minimum upstand in flexible standard wall construction 100mm. Outside of these minimum dimensions specific fire test evidence should be sought.  
All requirements of the Fire resistance field of application report from Warringtonfire, for the Selo product/s included in this drawing must be ensured, or an alternative fire assessment for any deviation including non-standard wall details must be sought from a competent and designated body for producing fire resistance assessments.

FOR FURTHER TECHNICAL DETAIL AND INFORMATION PLEASE  
CONTACT THE SALES TEAM AT sales@selo-uk.com

				Remove all burrs and sharp edges.				FINISH:	N/A		COLOUR:	N/A
				Please report errors and omissions			PROJECT:	LIGNA - PLASTERED			TOLERANCES IN mm UNLESS OTHERWISE NOTED	
				MATERIAL:	N/A			INT DWG NO:	SEL-DRW-PRD-LIGN-0002			
					NAME	DATE	EXT DWG NO:					X ± 1 X.X ±0.5 ANGULAR ±0.5 DEG
B	Wall build-up note added.	CK	29/7/22	DRAWN:	GT	10/8/21	DESCRIPTION:	SINGLE RH DOOR - PLASTERED FINISH			DO NOT SCALE PRINT	
A	Initial issue	GT	10/8/21	CHECKED:							MILLIMETERS	REV. <b>B</b>
REV:	COMMENT:	REVISED BY:	DATE:	APPROVED:				SCALE:	NTS	SHEET: 2 OF 2	