

selo®

EXCLUSIVE PRODUCT

***Nulfire***™

The *only* solution to achieve  
**fire-compliant doorsets**  
within **wall-lining systems**

**The answer for when  
Quadra+ Riser Doors are fitted  
within a wall-liner system and  
the rigid wall construction  
forms the fire-line.**

- ✓ Tested and Certified/Fire-rated up to E120
- ✓ Project the Doorset up to 80mm from the wall
- ✓ Compatible with Brickwork and Blockwork,  
as well as Cast Concrete walls



# **Nulfire™** doorset liners maintain the fire-line of a rigid wall...

Wall-lining systems are non fire-rated; this can be problematic when installing riser doors.

**Nulfire™** maintains the fire-line across the rigid wall construction and protects the riser door.



**Nulfire™**

**Nulfire™**

## Technical details

<b>Configuration</b>	Single or Double	<b>Wall Compatibility</b>	
<b>Min. Size</b>	450mm (h) x 250mm (w)	Brick and Block	Density: 600 - 1600 kg/m <sup>3</sup>
<b>Max. Size</b>	2400mm (h) x 950mm (w)	Lt wt Cast Concrete	Density: ≥ 2100 kg/m <sup>3</sup>
<b>Fire Rating</b>	Up to E120	Cast Concrete	Density: ≥ 2400 kg/m <sup>3</sup>
<b>Upstand Height</b>	Min. 100mm / Max. 280mm		

Rev 2.1 - December 2023  
SEL-MRK-00004



**Request a product demonstration:**

**call** 020 3880 0339 / **email** sales@selo-uk.com

Contact the Selo technical team to discuss your fire rating compliance requirements.



Scan to find  
out more



Connect with Selo

