

Operation & Maintenance

Please call for any further information 020 3880 0339.

Operation

Via Access Panels have either a centre lock operated by a square key, a 3-point lock, a 3-point lock secured by a keyed euro cylinder, or a touch catch.

The 3-point lock, (on its own), only requires the square key to gain access. The combined 3-point lock and euro cylinder requires the key to be turned in the euro cylinder first, which will, in-turn allow you to operate the 3-point lock with the square key and unlock the door.

COSHH

Via Access Panels do not require COSHH information as they are manufactured from steel, with no hazardous materials.

Cleaning

We recommend using a soft damp cloth with mild detergent on the powder coated finished doors. Do not use abrasive cleaners.

Fire Rated Doors **IMPORTANT**

Fire doors should be checked every **6 months minimum**.

Maintenance

Via Access Panels are a low maintenance unit. The parts to check on a regular basis are:

1. Lock

Ensure the lock operation is smooth and lubricated. If required use a small spray of light oil (e.g. WD40). *Fig.1*

2. Hinges

Ensure the hinges are smooth and quiet. If required use a small spray of light oil (e.g. WD40).

3. Seals

Check seals are correctly positioned and not broken.



Fig.1

Door components can be replaced if damaged, please contact the Selo team to request these.

call 020 3880 0339

email sales@selo-uk.com

For further information on the Selo product range, including installation videos, O&M manuals, and more, visit our website:

www.selo.global/resources

